

# S Series Checkweigher

## S 系列高性能重量检测机

- The fast speed and excellent precision models with a dynamic accuracy of up to  $\pm 0.1g$  and a weighing speed of up to 250 times per minute.
- Option of the belt width is 150/220/300/360/450mm, and the range is 200/1kg/4kg/10kg.
- With 232 weight feedback and pulse feedback, it supports label printing and filling screw adjustment.

- 高速和高精度机型，能够胜任高速高精度称重场合，动态精度最高可以达到  $\pm 0.1g$ ，称重速度最大支持每分钟250次。
- 带宽有150/220/300/360/450mm，量程有200g/1kg/4kg/10kg可选。
- 带232重量和脉冲反馈，支持贴标打印和粉体螺杆调节。



Model 型号/SW	150(220) -D20	220(300) -D28	300(360) -D32	360(450) -D40	Other 其他规格
Weighing Range 量程(g)	2~1000 (max 1200)	2~1000 (max 1200)	2~3000 (max 4000)	3~10000	Details please refer to the model sheet or Customized 详见选型目录 或定制
Minimum Scale 最小刻度 (g)	0.1	0.1	0.1	1	
Best Accuracy 最佳精度 (g)	$\pm 0.1$	$\pm 0.3$	$\pm 0.5$	$\pm 5$	
Max Throughput 最大通过量(pcs/min)	250	150	100	60	
Parameter Setting 参数设置	By intelligent product learning 智能自学习				
Weight Belt Width 称重皮带宽度(mm)	150(220)	220(300)	220(300)	360(450)	
Weight Belt Length 称重皮带长度(mm)	250/350/450	350/450/550	350/450/550	550/700	
Belt Height 皮带离地高度(mm)	700-820/780-900 or Customized 或定制				
Alarm Mode 报警模式	Aural and visual 声光报警				
Rejection Option 剔除器类型	Air Jet, Pusher, Flipper, Flap Down, Down Belt 气吹/推杆/摆臂/翻板/皮带下坠				